

# Intrepid 6A

## Full-featured RF system for 6-foot door openings

Combining superb detection rate with the Active Response System that automatically adjusts the system to block interference, Intrepid 6A is a reliable workhorse in the fight against shrink.

The modern, acrylic design blends into any store environment. The optional people counter can provide useful store analytics, while the remote tuning capabilities help with reducing the total cost of ownership.

### KEY FEATURES

- > Elegant acrylic design
- > Active Response System monitors store environment and automatically adjusts the system to reduce interference
- > Can be synchronized with multiple systems
- > Network connection and I/O port for easy integration with other LP systems
- > Remote tuning capability reduces maintenance costs and downtime
- > Optional people counter can help store operations and scheduling

### SPECIFICATIONS

- > Frequency: 8.2 MHz
- > Dimensions: 12.8" W x 59.4" H x 0.8" D (32.5 cm x 151 cm x 2 cm)
- > Base depth: 4.1" (10.5 cm)
- > Weight: 30.8 lbs (14 kg)
- > Order code: CT320 RF TRX
- > Detection range: Up to 6' (between two pedestals)
- > Power requirement: 48V DC/15W per pedestal
- > Alarm mode: Buzzer and RGB alarm indicator
- > Operating temperature: 32° F - 95° F
- > Relative humidity range: 0 - 90%, non-condensing

